

軸流ファンAxial Fan

SEPA

□25×25×10mm



PERFORMANCE

产品型号	输入电压 (V)	使用电压 范围(V)	电流(A)		转速 (RPM)	风量		风压		噪音 dBA	Life(h) 20℃
			Locked	Moved		CMM	CFM	Pa	mmH2O		
MF25A05	5	4.5~5.5	0.20	0.070	6000	0.022	0.80	9.8	1.00	10	30000
MF25A05H	5	4.5~5.5	0.22	0.085	7700	0.027	1.00	16.7	1.70	13	30000
MF25A12	12	10.2~13.8	0.20	0.060	9500	0.032	1.10	22.6	2.31	18	30000
MFB25A05	5	4.5~5.5	0.20	0.070	7700	0.027	1.00	16.7	1.70	15	50000
MFB25A05H	5	4.5~5.5	0.22	0.085	8500	0.032	1.10	22.6	2.31	17	50000
MFB25A12	12	10.2~13.8	0.20	0.060	10600	0.038	1.30	31.4	3.20	22	50000
SF25A05	5	4.5~5.5	0.22	0.070	6000	0.022	0.80	9.8	1.00	5	30000
SF25A05H	5	4.5~5.5	0.25	0.090	7700	0.027	1.00	16.7	1.70	9	30000
SF25A12	12	10.2~13.8	0.20	0.040	7700	0.027	1.00	16.7	1.70	9	30000
SFB25A05	5	4.5~5.5	0.22	0.060	7700	0.027	1.00	16.7	1.70	10	50000
SFB25A05H	5	4.5~5.5	0.25	0.080	8500	0.032	1.10	22.6	2.31	15	50000
SFB25A12	12	10.2~13.8	0.20	0.040	8400	0.029	1.00	19.6	2.00	14	50000

※ Operating Temperature (°C) -10 ~ +60

SHAPE&DIMENSIN

※ Operating Voltage (V) 5V: 4.5 ~ 5.5 12V: 10.2 ~ 13.8

Lead Wire AWG 28

風量静压特性 AIR FLOW VS AIR PRESSURE 形状及び寸法 SHAPE&DIMENSION

