

軸流ファン Axial Fan

SEPA

□ 40×40×10mm



PERFORMANCE

产品型号	输入电压 (V)	使用电压 范围(V)	电流(A)		转速 (RPM)	风量		风压		噪音 dBA	Life(h))20℃
			Locked	Moved		CMM	CFM	Pa	mmH2O		
MF40D05	5	4.5~5.5	0.21	0.130	4700	0.07	2.50	17.7	1.81	15	20000
MF40D09	9	8.0~11.0	0.12	0.090	4500	0.07	2.50	15.7	1.60	12	20000
MF40D12	12	10.2~13.8	0.11	0.080	5100	0.08	2.80	20.6	2.10	13	20000
MF40D12H	12	10.2~13.8	0.14	0.080	6700	0.100	3.50	34.3	3.50	24	20000
MFB40D05	5	4.5~5.5	0.21	0.130	5600	0.08	2.80	22.6	2.31	18	40000
MFB40D12	12	10.2~13.8	0.11	0.080	6200	0.09	3.20	30.4	3.10	20	40000
MFB40D12H	12	10.2~13.8	0.14	0.080	7700	0.11	3.90	48.1	4.91	28	40000

※ Operating Temperature (°C) -10 ~ +60

SHAPE&DIMENSIN

※ Operating Voltage (V) 5V: 4.5 ~ 5.5 9V: 8.0 ~ 11.0 12V: 10.2 ~ 13.8

Lead Wire AWG 28

风量静压特性 AIR FLOW VS AIR PRESSURE 形状及び寸法 SHAPE&DIMENSION

