

軸流ファン Axial Fan

SEPA

□40×40×16mm



PERFORMANCE

| 产品型号 | 输入电压 (V) | 使用电压 范围(V) | 电流(A) | | 转速 (RPM) | 风量 | | 风压 | | 噪音 dBA | Life(h))20℃ |
|-----------|----------|------------|--------|-------|----------|-------|------|------|-------|--------|--------------|
| | | | Locked | Moved | | CMM | CFM | Pa | mmH2O | | |
| MF40C05 | 5 | 4.5~5.5 | 0.29 | 0.130 | 5000 | 0.1 | 3.50 | 22.6 | 2.31 | 13 | 30000 |
| MF40C12H | 12 | 10.2~13.8 | 0.25 | 0.080 | 7700 | 0.15 | 5.30 | 52 | 5.31 | 23 | 30000 |
| MF40C24H | 24 | 20.4~27.6 | 0.13 | 0.040 | 7700 | 0.15 | 5.30 | 52 | 5.31 | 23 | 30000 |
| MFB40C05 | 5 | 4.5~5.5 | 0.29 | 0.130 | 5000 | 0.100 | 3.50 | 22.6 | 2.31 | 13 | 40000 |
| MFB40C12H | 12 | 10.2~13.8 | 0.25 | 0.080 | 7700 | 0.15 | 5.30 | 52 | 5.31 | 24 | 40000 |
| MFB40C24H | 24 | 20.4~27.6 | 0.13 | 0.040 | 7700 | 0.15 | 5.30 | 52 | 5.31 | 24 | 40000 |

※ Operating Temperature (°C) -10 ~ +60

SHAPE&DIMENSIN

※ Operating Voltage (V) 5V: 4.5 ~ 5.5 12V: 10.2 ~ 13.8 24V: 20.4 ~ 27.6

Lead Wire AWG 28

风量静压特性 AIR FLOW VS AIR PRESSURE

形状及び寸法 SHAPE&DIMENSION

