

# 軸流ファン Axial Fan

# SEPA

□ 60×60×16mm



## PERFORMANCE

产品型号	输入电压 (V)	使用电压 范围(V)	电流(A)		转速 (RPM)	风量		风压		噪音 dBA	Life(h) 20℃
			Locked	Moved		CMM	CFM	Pa	mmH2O		
MF60B05	5	4.5~5.5	0.25	0.150	2800	0.25	8.80	15.7	1.60	17	30000
MF60B12L	12	10.2~13.8	0.12	0.055	2900	0.26	9.20	16.7	1.70	17	30000
MF60B12H	12	10.2~13.8	0.22	0.090	3800	0.35	12.40	28.4	2.90	22	30000
MF60B24L	24	20.4~27.6	0.07	0.030	2900	0.260	9.20	16.7	1.70	17	30000
MF60B24H	24	20.4~27.6	0.11	0.050	3800	0.35	12.40	28.4	2.90	22	30000
MFB60B05	5	4.5~5.5	0.25	0.150	2800	0.25	8.80	15.7	1.60	18	50000
MFB60B12L	12	10.2~13.8	0.12	0.055	2900	0.26	9.20	16.7	1.70	18	50000
MFB60B12H	12	10.2~13.8	0.22	0.090	3800	0.35	12.40	28.4	2.90	23	50000
MFB60B24L	24	20.4~27.6	0.07	0.030	2900	0.260	9.20	16.7	1.70	18	50000
MFB60B24H	24	20.4~27.6	0.11	0.050	3800	0.35	12.40	28.4	2.90	23	50000

※ Operating Temperature (°C) -10 ~ +60

SHAPE&DIMENSIN

※ Operating Voltage (V) 5V: 4.5 ~ 5.5 12V: 10.2 ~ 13.8 24V: 20.4 ~ 27.6

Lead Wire AWG 28

风量静压特性 AIR FLOW VS AIR PRESSURE

形状及び寸法 SHAPE&DIMENSION

