

軸流ファン Axial Fan

60×60×25mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 7 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 70g (2.46oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DT1206L	B	12	5~13.8	0.08	0.96	2600	0.34	12.00	1.80	0.071	20.0
DT1206M	B	12	5~13.8	0.10	1.20	3000	0.40	14.10	2.50	0.098	23.0
DT1206H	B	12	5~13.8	0.14	1.68	3800	0.50	17.70	3.60	0.142	27.0
DT1206G	B	12	5~13.8	0.17	2.04	4200	0.60	21.20	5.00	0.197	30.0
DT1206U	B	12	5~13.8	0.25	3.00	5200	0.72	25.50	7.00	0.276	36.0

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

