

軸流ファン Axial Fan

60×60×25mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 7 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 63g (2.218oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DK1206G	N	12	5~13.8	0.10	1.20	3800	0.50	17.70	3.60	0.142	25.0
DK1206U	N	12	5~13.8	0.15	1.80	4200	0.60	21.20	5.00	0.197	29.0
DK1206U1	N	12	5~13.8	0.20	2.40	4700	0.72	25.50	7.00	0.276	32.0

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

