

軸流ファン Axial Fan

60×60×25mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 11 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 55g (1.94oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4 holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DR1207L	B	12	5~13.8	0.08	0.96	2800	0.56	19.80	2.60	0.102	27.0
DR1207M	B	12	5~13.8	0.12	1.44	3400	0.65	23.00	3.70	0.146	31.0
DR1207H	B	12	5~13.8	0.18	2.16	3800	0.72	25.20	4.30	0.169	34.5
DR1207G	B	12	5~13.8	0.20	2.40	4200	0.79	27.90	5.20	0.205	36.5

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

