

# 軸流ファン Axial Fan

## 60×60×25mm SERIES



- \* Material Impeller & Frame : Plastic (UL 94V-0)
- \* Lead Wires : UL 1007AWG # 24 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 11 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 55g ( 1.94oz )

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type ( 3 holes )  
T : Rib Type ( 4 holes )  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m <sup>3</sup> /min	CFM	mm Aq	IN Aq	dB-A
DR1207L	S	12	5~13.8	0.08	0.96	2800	0.56	19.80	2.60	0.102	26.0
DR1207M	S	12	5~13.8	0.12	1.44	3400	0.65	23.00	3.70	0.146	30.0
DR1207H	S	12	5~13.8	0.18	2.16	3800	0.72	25.20	4.30	0.169	33.2
DR1207G	S	12	5~13.8	0.20	2.40	4200	0.79	27.90	5.20	0.205	35.0

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air;  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

