

軸流ファン Axial Fan

80×80×20mm SERIES



- *Material Impeller & Frame : Plastic (UL 94V-0)
- *Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- *Impeller : 7 Blades
- *Rotational direction CCW view from inlet face
- *Weight : 63g (2.218oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DG1208L	S	12	5~13.8	0.10	1.20	2000	0.70	24.80	1.82	0.071	25.2
DG1208M	S	12	5~13.8	0.16	1.92	2500	0.81	28.70	2.65	0.104	29.5
DG1208H	S	12	5~13.8	0.22	2.64	3100	1.01	35.40	2.89	0.113	34.5

- *Function type is optional
- *The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- *Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- *All readings are typical values at rated voltage.
- *Specifications are subject to change without notice.

