

# 軸流ファン Axial Fan

## 80×80×25mm SERIES



- \* Material Impeller & Frame : Plastic (UL 94V-0)
- \* Lead Wires : UL 1007AWG # 24 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 7 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 90g (3.17oz)

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type (8 holes)  
T : Rib Type (4holes)  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m <sup>3</sup> /min	CFM	mm Aq	IN Aq	dB-A
DT1208L	B	12	5~13.8	0.10	1.20	2000	0.75	26.50	1.70	0.067	21.0
DT1208M	B	12	5~13.8	0.13	1.56	2400	0.90	31.80	2.50	0.098	26.0
DT1208H	B	12	5~13.8	0.15	1.80	2900	1.05	37.10	3.40	0.134	30.0
DT1208G	B	12	5~13.8	0.22	2.64	3400	1.25	44.10	4.80	0.189	34.0
DT1208U	B	12	5~13.8	0.48	5.76	4200	1.70	60.00	8.00	0.315	38.5

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air;  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

