

# 軸流ファン Axial Fan

## 80×80×25mm SERIES



- \* Material Impeller & Frame : Plastic (UL 94V-0)
- \* Lead Wires : UL 1007AWG # 24 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 7 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 82g (2.887oz)

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type ( 8 holes )  
T : Rib Type ( 4holes )  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m <sup>3</sup> /min	CFM	mm Aq	IN Aq	dB-A
DT1208L	S	12	5~13.8	0.11	1.32	2000	0.66	23.30	1.53	0.060	25.5
DT1208M	S	12	5~13.8	0.13	1.56	2400	0.82	28.80	2.11	0.083	28.9
DT1208H	S	12	5~13.8	0.17	2.04	2800	0.94	33.00	2.68	0.106	31.8

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air,  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

