

# 軸流ファン Axial Fan

## 80×80×25mm SERIES



- \* Material Impeller & Frame : Plastic (UL 94V-0)
- \* Lead Wires : UL 1007AWG # 24 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 7 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 75g ( 2.64oz )

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type ( 8 holes )  
T : Rib Type ( 4holes )  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m <sup>3</sup> /min	CFM	mm Aq	IN Aq	dB-A
DK1208L	S	12	5~13.8	0.06	0.72	2000	0.70	24.80	1.54	0.063	22.7
DK1208M	S	12	5~13.8	0.09	1.08	2400	0.86	30.20	2.26	0.092	25.2
DK1208H	S	12	5~13.8	0.13	1.56	2800	1.02	36.00	3.01	0.123	28.4
DK1208G	S	12	5~13.8	0.23	2.76	3200	1.17	41.40	3.79	0.154	31.4
DK1208U	S	12	5~13.8	0.34	4.08	3600	1.29	45.60	4.31	0.176	34.2

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air;  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

