

軸流ファン Axial Fan

80×80×25mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 7 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 82g (2.887oz)
- * Life Time : AT 80°C 10000Hus

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4holes)
Other Specialty Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DT1208L(T)	N	12	5~13.8	0.11	1.32	1800	0.64	22.50	1.19	0.047	22.0
DT1208M(T)	N	12	5~13.8	0.15	1.80	2100	0.78	27.50	1.56	0.061	23.8
DT1208H(T)	N	12	5~13.8	0.19	2.28	2600	0.98	34.60	2.28	0.090	28.8
DT1208G(T)	N	12	5~13.8	0.28	3.36	3100	1.17	41.20	3.12	0.123	32.7

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

