

# 軸流ファン Axial Fan

## 80×80×25mm SERIES



- \* Material Impeller & Frame : Plastic (UL 94V-0)
- \* Lead Wires : UL 1007AWG # 24 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 7 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 75g (2.641oz)

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
Frame Type : P : Flange Type ( 8 holes )  
T : Rib Type ( 4 holes )  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m <sup>3</sup> /min	CFM	mm Aq	IN Aq	dB-A
DT2408L	B	24	10.8~28	0.04	0.96	2000	0.74	26.00	1.40	0.055	24.4
DT2408M	B	24	10.8~28	0.05	1.20	2300	0.85	30.00	2.11	0.083	27.5
DT2408H	B	24	10.8~28	0.10	2.40	2800	1.05	37.00	2.85	0.112	31.9
DT2408G	B	24	10.8~28	0.16	3.84	3300	1.25	44.00	3.56	0.140	35.5

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air;  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

