

軸流ファン Axial Fan

80×80×25mm PWM SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
 Red Wire Positive (+) Yellow Wire (FG)
 Black Wire Negative (-) Green Wire (PWM)
- * Impeller : 7 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 90g (3.17oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
 N : Nanometer Bearing F, IB IS
Frame Type : P : Flange Type (8 holes)
 T : Rib Type (4holes)
 Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DK1208L	B	12	10.8~13.8	0.15	1.80	3000	1.25	44.00	5.00	0.197	31.5
DK1208M	B	12	10.8~13.8	0.32	3.84	4000	1.60	56.20	7.50	0.295	37.2
DK1208H	B	12	10.8~13.8	0.50	6.00	4800	1.91	67.20	10.17	0.400	41.5

- * Function type is optional.
- * The max. air flow and the speed are measured in free air;
 max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
 one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

