

軸流ファン Axial Fan

92×92×25mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 7 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 95g (3.35oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4 holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DT1209L	B	12	5~13.8	0.07	0.84	1750	0.80	28.20	1.50	0.059	20.0
DT1209M	B	12	5~13.8	0.12	1.44	2200	1.00	35.30	2.30	0.091	26.0
DT1209H	B	12	5~13.8	0.17	2.04	2700	1.20	42.30	3.10	0.122	30.0
DT1209G	B	12	5~13.8	0.25	3.00	3100	1.40	50.00	4.00	0.157	38.0
DT1209U	B	12	5~13.8	0.40	4.80	3500	1.55	54.70	4.80	0.189	40.0

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

