

軸流ファン Axial Fan

92×92×25mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 7 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 99g (3.486oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4 holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DT1209L	S	12	5~13.8	0.12	1.44	2000	1.04	36.60	2.06	0.084	25.7
DT1209M	S	12	5~13.8	0.16	1.92	2400	1.20	42.20	2.64	0.107	28.2
DT1209H	S	12	5~13.8	0.22	2.64	2800	1.39	49.10	3.25	0.132	32.8
DT1209G	S	12	5~13.8	0.30	3.60	3300	1.70	60.00	4.50	0.177	39.5

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

