

軸流ファン Axial Fan

92×92×25mm PWM SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 24 or Equivalent
 Red Wire Positive (+) Yellow Wire (FG)
 Black Wire Negative (-) Green Wire (PWM)
- * Impeller : 7 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 95g (3.35oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
 N : Nanometer Bearing F : 1B 1S
Frame Type : P : Flange Type (8 holes)
 T : Rib Type (4holes)
 Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DT1209L	B	12	5~13.8	0.20	2.40	2500	1.40	49.40	2.65	0.104	30.2
DT1209M	B	12	5~13.8	0.38	4.56	3600	2.10	74.20	5.05	0.198	40.5
DT1209H	B	12	5~13.8	0.45	5.40	4200	2.33	82.00	5.40	0.212	43.0

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
 max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
 one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

