

# 軸流ファン Axial Fan

## 120×120×25mm SERIES



- \*Material Impeller & Frame : Plastic (UL 94V-0)
- \*Lead Wires : UL 1007AWG # 24 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \*Impeller : 7 Blades
- \*Rotational direction CCW view from inlet face
- \*Weight : 121g (4.26oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
Frame Type : P : Flange Type (8 holes)  
T : Rib Type (4 holes)  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.F	VDC	VDC	Amp	Watt	R.P.M	m <sup>3</sup> /min	CFM	mm Aq	INAq	dB-A
DT1212L	S	12	5~13.8	0.18	2.16	1700	1.81	64.00	1.66	0.065	28.0
DT1212M	S	12	5~13.8	0.23	2.76	2000	2.18	77.00	2.73	0.107	31.0
DT1212H	S	12	5~13.8	0.45	6.00	2300	2.60	92.00	3.61	0.142	34.0

- \*Function type is optional
- \*The max. air flow and the speed are measured in free air;  
max Air pressure is measured at zero air flow.
- \*Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \*All readings are typical values at rated voltage.
- \*Specifications are subject to change without notice.

