

軸流ファン Axial Fan

40×40×28mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 26 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 5 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 46g (1.62oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4holes)
Other Specially Design Type

| 型号 | 轴承 | 输入电压 | 电压范围 | 电流 | 功率 | 转速 | 风量 | 风压 | 噪音 | | |
|-----------|-----------|------|--------|------|------|-----------|---------------------|-------|-------|-------|------|
| PART NO. | B . S . N | VDC | VDC | Amp | Watt | R . P . M | m ³ /min | CFM | mm Aq | INAq | dB-A |
| DXL1204U | B | 12 | 5~13.8 | 0.45 | 5.40 | 14000 | 0.57 | 20.30 | 29.80 | 1.173 | 49.0 |
| DXL1204S1 | B | 12 | 5~13.8 | 0.69 | 8.28 | 16000 | 0.66 | 23.30 | 33.50 | 1.319 | 53.0 |

- *Function type is optional
- *The max. air flow and the speed are measured in free air,
max Air pressure is measured at zero air flow.
- *Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- *All readings are typical values at rated voltage.
- *Specifications are subject to change without notice.

