

軸流ファン Axial Fan

40×40×28mm PWM SERIES



- *Material Impeller & Frame : Plastic (UL 94V-0)
- *Lead Wires : UL 1007AWG # 26 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- *Impeller : 5 Blades
- *Rotational direction CCW view from inlet face
- *Weight : 46g (1.62oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4 holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	INAq	dB-A
DXL1204L	B	12	10.8~13.8	0.30	3.60	10600	0.44	15.50	14.50	0.571	40.5
DXL1204M	B	12	10.8~13.8	0.45	5.40	13600	0.55	19.40	29.50	1.161	48.5
DXL1204H	B	12	10.8~13.8	0.69	8.40	16000	0.66	23.30	38.50	1.516	54.0

- *Function type is optional
- *The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- *Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- *All readings are typical values at rated voltage.
- *Specifications are subject to change without notice.

