

軸流ファン Axial Fan

40×40×56mm PWM SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wire : UL 1007AWG # 26 or Equivalent
 Red Wire Positive (+) Yellow Wire (FG)
 Black Wire Negative (-) Green Wire (PWM)
- * Impeller : 5 Blades(inlet), 5 Blades(outlet)
- * Rotational direction CCW view from inlet face
- * Weight : 92g (3.24oz)

SPECIFICATION : R : 2 Ball Bearings S : Sleeve
 N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
 T : Rib Type (4holes)
 Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m ³ /min	CFM	mm Aq	IN Aq	dB-A
DX2L1204L	B	12	5~13.8	1.00	12.00	10600/ 9000	0.58	20.40	20.52	0.808	44.5
DX2L1204M	B	12	5~13.8	1.20	14.40	13600/ 11600	0.72	25.30	31.50	1.240	54.5
DX2L1204H	B	12	5~13.8	1.50	18.00	16000/ 13600	0.88	28.50	28.50	1.870	62.5

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
 max Air pressure is measured at zero air flow
- * Noise is measured in semi anechoic chamber in free air,
 one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

