

# 軸流ファン Axial Fan

## 50×50×10mm SERIES



- \* Material Impeller & Frame : Plastic (UL 94V-0)
- \* Lead Wires : UL 1007AWG # 24 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 11 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 25g (0.880oz)

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type ( 8 holes )  
T : Rib Type ( 4 holes )  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B . S . N	VDC	VDC	Amp	Watt	R . P . M	m <sup>3</sup> /min	CFM	mm Aq	INAq	dB-A
DX1205L	B	12	5~13.8	0.06	0.72	3500	0.22	7.80	1.40	0.055	23.0
DX1205M	B	12	5~13.8	0.09	1.08	4500	0.25	8.80	2.10	0.083	28.0
DX1205H	B	12	5~13.8	0.10	1.20	5000	0.27	9.50	2.30	0.091	31.0
DX1205G	B	12	5~13.8	0.13	1.56	5500	0.28	9.90	2.50	0.098	35.0

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air,  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

