

軸流ファン Axial Fan

60×60×15mm SERIES



- * Material Impeller & Frame : Plastic (UL 94V-0)
- * Lead Wires : UL 1007AWG # 26 or Equivalent
Red Wire Positive (+)
Black Wire Negative (-)
- * Impeller : 9 Blades
- * Rotational direction CCW view from inlet face
- * Weight : 45g (1.585oz)

SPECIFICATION : B : 2 Ball Bearings S : Sleeve
N : Nanometer Bearing
Frame Type : P : Flange Type (8 holes)
T : Rib Type (4 holes)
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量		风压		噪音
PART NO.	B . S . N	VDC	VDC	Amp	Watt	R . P . M	m ³ /min	CFM	mm Aq	INAq	dB-A
DR1206L	N	12	5~13.8	0.10	1.20	3000	0.41	15.00	1.87	0.074	24.5
DR1206M	N	12	5~13.8	0.13	1.56	3600	0.50	18.00	3.03	0.119	27.8
DR1206H	N	12	5~13.8	0.18	2.16	4200	0.60	21.00	4.04	0.159	32.8
DR1206G	N	12	5~13.8	0.28	3.36	4800	0.73	26.00	4.84	0.191	35.2

- * Function type is optional
- * The max. air flow and the speed are measured in free air;
max Air pressure is measured at zero air flow.
- * Noise is measured in semi anechoic chamber in free air,
one meter from intake side.
- * All readings are typical values at rated voltage.
- * Specifications are subject to change without notice.

