

# 軸流ファン Axial Fan

## 60×60×15mm SERIES



- \* Material Impeller & Frame : Plastic ( UL 94V-0)
- \* Lead Wires : UL 1007AWG # 26 or Equivalent  
Red Wire Positive (+)  
Black Wire Negative (-)
- \* Impeller : 9 Blades
- \* Rotational direction CCW view from inlet face
- \* Weight : 45g ( 1.585oz)

**SPECIFICATION :** B : 2 Ball Bearings S : Sleeve  
N : Nanometer Bearing  
**Frame Type :** P : Flange Type ( 8 holes )  
T : Rib Type ( 4holes )  
Other Specially Design Type

型号	轴承	输入电压	电压范围	电流	功率	转速	风量	风压	噪音		
PART NO.	B.S.N	VDC	VDC	Amp	Watt	R.P.M	m <sup>3</sup> /min	CFM	mm Aq	IN Aq	dB-A
DR1206L	B	12	5~13.8	0.08	0.96	3000	0.41	15.00	1.87	0.074	25.5
DR1206M	B	12	5~13.8	0.11	1.32	3600	0.50	18.00	3.03	0.119	28.8
DR1206H	B	12	5~13.8	0.15	1.80	4200	0.60	21.00	4.04	0.159	34.0
DR1206G	B	12	5~13.8	0.26	3.12	4800	0.73	26.00	4.84	0.191	36.4
DR1206U	B	12	5~13.8	0.29	3.48	5400	0.88	31.00	5.83	0.230	38.6

- \* Function type is optional
- \* The max. air flow and the speed are measured in free air;  
max Air pressure is measured at zero air flow.
- \* Noise is measured in semi anechoic chamber in free air,  
one meter from intake side.
- \* All readings are typical values at rated voltage.
- \* Specifications are subject to change without notice.

